



First of all, Thanks for purchasing this product. We hope you are very satisfied with this product. Installation can be a bit tricky, so this guide should be helpful. We'll do it in steps, shall we?

You will need: Superglue, sandpaper square, alcohol swab, a 1/16" drill-bit (these materials **are** included in the kit), electric drill, a fine flat-head screwdriver, a rag and a clothespin/clamp (these items not included).


1. The First step is to prepare the area. Since there will be superglue involved, I would recommend covering your seats with newspaper, towels, or an old blanket just to be safe. Once covered, pull out the shade to its full extension and use a rag to keep it from retracting as shown below – It should hang freely. You will need both hands for the following steps.



2. Likely, your clip broke off in the way most of them do and there is still a section left with an indented surface in which the new clip will fit. However, before you glue the new clip into place, the surface must be scored a bit which you can do with the included sandpaper as shown (a rough surface will hold the glue better than a perfectly flat surface). Lastly, you will need to clean the area of dirt and sanding dust so that it is clear of debris. You can use the included alcohol swab for this purpose.




3. Now you are ready to begin the installation process. First, use the included glue and secure the clip into place. You may need to use a clamp or a clothespin to keep it in place while drying. It is very important to give the glue enough time to dry.



4. Once the glue has dried, it is time for the last step: securing the clip with the small screw included in the kit. Be careful as these suckers are hard to find if you drop them in your interior! Carefully drill a shallow hole for the screw with the bit provided as shown- just enough to get it started- and use a fine screwdriver to gently tighten the screw. Be very careful as you DO NOT want to crack the plastic on the other side. If you feel you are doing so, you can leave the screw partially tightened as it will still serve its purpose, have plenty of clearance, & be out of view. And you're done!!

Cheers!!



That looks great!

Questions? Problems? Need more kits? Let us know



IF YOU LOVE IT, PLEASE SPREAD THE WORD & TELL YOUR DISCO BUDDIES!!!!!!

Enjoy!